

---

## **Design Considerations for a Half Impulse Radiating Antenna**

**Everett G. Farr et al.**

**Farr Research  
614 Paseo Del Mar NE  
Albuquerque, NM 87123**

**January 1996**

**Final Report**

**APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.**

**19970717 225**

**DTIC QUALITY INSPECTED 3**



**PHILLIPS LABORATORY  
Advanced Weapons and Survivability Directorate  
AIR FORCE MATERIEL COMMAND  
KIRTLAND AIR FORCE BASE, NM 87117-5776**

---

Using Government drawings, specifications, or other data included in this document for any purpose other than Government procurement does not in any way obligate the U.S. Government. The fact that the Government formulated or supplied the drawings, specifications, or other data, does not license the holder or any other person or corporation; or convey any rights or permission to manufacture, use, or sell any patented invention that may relate to them.

This report has been reviewed by the Public Affairs Office and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nationals.

If you change your address, wish to be removed from this mailing list, or your organization no longer employs the addressee, please notify PL/WSQW, 3550 Aberdeen Ave SE, Kirtland AFB, NM 87117-5776.


Do not return copies of this report unless contractual obligations or notice on a specific document requires it's return.

This report has been approved for publication.




WILLIAM D PRATHER, GS-14  
Project Manager

FOR THE COMMANDER



DR TOM HUSSEY, GS-15  
Chief, High Energy Sources  
Division



WILLIAM G HECKATHORN, COL, USAF  
Director, Advanced Weapons and Survivability  
Directorate

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE January 1996		3. REPORT TYPE AND DATES COVERED Final Report, Mar 1995 - Jan 1996
4. TITLE AND SUBTITLE Design Considerations for a Half Impulse Radiating Antenna		5. FUNDING NUMBERS C: F29601-95-C-0106 PE:65502F PR:3005 TA:CO WU:KZ		
6. AUTHOR(S) Everett G Farr, Gary D Sower, and Lanney M Atchley				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Farr Research, 614 Paseo Del Mar NE, Albuquerque, NM 87123		8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Phillips Laboratory/WSQ, 3550 Aberdeen Avenue SE, Kirtland AFB, NM 87117-5776		10. SPONSORING/MONITORING AGENCY REPORT NUMBER PL-TR-97-1058		
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for Public Release; Distribution is Unlimited			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 Words) Recently developed pulsers have the capability to generate approximately 100GW of peak power with an impulse width of about 150 ps Full Width Half Max, and with a repetition rate of about 1 kHz. However, all these hydrogen-gap pulsers produce output into a coaxial waveguide, which is a single-ended configuration. This configuration is difficult to match to an antenna, since most free-space antenna designs require a balanced feed. One can convert the signal to a balanced configuration with a coaxial unzipper or point geometry converter, but there may be losses associated with these transitions. An alternative is to feed the signal into half a reflector Impulse Radiating Antenna (IRA). For this project, we developed the design principles of half reflector IRAs, and we calculated the radiated far field. We also provided a design for the lens that converts a coaxial Transverse Electromagnetic (TEM) mode to a spherical wave on the feed arms. Finally, we provided measurements of a ground-plane model of a half reflector IRA. The results of this project have already been summarized in two Sensor and Simulation Notes and a Prototype IRA memo, so we only very briefly summarized their contents.				
14. SUBJECT TERMS Half Impulse Radiating Antenna, Ultrawideband Antennas, High-Voltage, Lens			15. NUMBER OF PAGES 18	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UNLIMITED	

## TABLE OF CONTENTS

Report Documentation.....	i/ii
Table of Contents.....	iii
List of Figures.....	iv
Preface.....	v
<u>Section</u>	
1.0 Introduction.....	1
2.0 Balun Design Principles.....	2
3.0 Lens design principles.....	4
4.0 Radiated Fields.....	5
5.0 Measurements.....	7
6.0 Conclusion.....	9
Distribution list.....	10

## FIGURES

<u>Figure</u>		<u>Page</u>
1.	A sketch of the Half IRA, shown here with an oil cap.	2
2.	Two lens designs, with an oil cap (left) and without an oil cap (right).	3
3.	Improved oil-lens-air design using $\Delta\theta_1 = 43^\circ$ , and $\Psi_2/\Psi_1 = 2$ .	4
4.	Radiated field on boresight for a 2 m diameter half IRA driven by a 150 ps source.	5
5.	Fast part of the H-plane (top) and E-plane (bottom) radiated field for the half IRA.	6
6.	A comparison of the boresight predicted and measured fields for a Half IRA.	8

## PREFACE

Many helpful discussions were held with Carl E Baum, James P O'Laughlin, and C Jerald Buchenauer, of Phillips Laboratory. Their assistance is gratefully acknowledged.

DTIC QUALITY INSPECTED 3

## 1.0 INTRODUCTION

Recently developed pulsed have the capability to generate approximately 100 GW of peak power with an impulse width of about 150 ps Full Width Half Max, and with a repetition rate of about 1 kHz. However, all these hydrogen-gap pulsed produce output into a coaxial waveguide, which is a single-ended configuration. This configuration is difficult to match to an antenna, since most free-space antenna designs require a balanced feed. One can convert the signal to a balanced configuration with a coaxial unzipper [1] or point geometry converter, but there may be losses associated with these transitions. An alternative is to feed the signal into half a reflector Impulse Radiating Antenna, as first suggested in [2]. For this project, we developed the design principles of half reflector Impulse Radiating Antennas, and we calculate the radiated far field. We also provided a design for the lens that converts a coaxial TEM mode to a spherical wave on the feed arms. The results of this project have already been summarized in two Sensor and Simulation Notes, so here we very briefly summarize their contents.

---

11 E. G. Farr, et al, Design Considerations for Ultra-Wideband, High-Voltage Baluns, Sensor and Simulation Note 371, October 1994.

2. C. E. Baum, Variations on the Impulse Radiating Antenna Theme, Sensor and Simulation Note 378, February 1995.

## 2.0 GENERAL DESIGN

We consider here a strategy for radiating a high-power single-ended transient source using a Half-Impulse Radiating Antenna (Half IRA). An example of a source we might wish to radiate with such an antenna is the HASP or H4 pulser currently being developed by Phillips Lab. The output of the H4 is a pulse with about 100 GW of peak power into a coaxial line. The pulse width is approximately 150 ps Full Width Half Max, and the source has a repetition rate of about 1 kHz.

A sketch of the proposed antenna is shown in Figure 1. For simplicity, we have assumed an  $F/D$  of 0.25. The feed impedance of the two arms combined is 100 ohms in air. Note that these arms are the same angular width ( $\pm 4^\circ$  from the cone center) as would be normally used in standard full IRA configurations, in which a single pair of arms with a full reflector has an impedance of  $400\ \Omega$ . The lens is designed using the principles contained in [3]. An oil cap may or may not be used, depending upon dielectric breakdown considerations near the feed point. Configurations both with and without the oil cap are shown in Figure 2.




Figure 1. A sketch of the Half IRA, shown here with an oil cap.






Figure 2. Two lens designs, with an oil cap (left) and without an oil cap (right).

### 3.0 LENS DESIGN PRINCIPLES

A key problem in the design is how to convert the coaxial wave mode to a spherical wave. We have developed a solution to this problem in [3]. The equations are derived in [3], so we simply show here a sample solution to the equations, as shown in Figure 3. This lens converts a coaxial mode on the left, to a spherical wave on the right.




Figure 3. Improved oil-lens-air design using  $\Delta\theta_1 = 43^\circ$ , and  $\Psi_2/\Psi_1 = 2$ .

3. E G. Farr and C. E. Baum, Feed-Point Lenses for Half Reflector IRAs, Sensor and Simulation Note 385, November 1995.

#### 4.0 RADIATED FIELDS

The principles behind the field radiated from a half IRA were also developed. We adapted earlier calculations of a full IRA to that of a half IRA. An example of the boresight radiated field is shown in Figure 4. Furthermore, the radiated field as a function of angle off-boresight in the H- and E-planes is shown in Figure 5. We leave the details of the calculation to [4].




Figure 4. Radiated field on boresight for a 2 m diameter half IRA driven by a 150 ps risetime source. The peak is 4.6, with a  $t_{FWHM}$  of 139 ps.





Figure 5. Fast part of the H-plane (top) and E-plane (bottom) radiated field for the half reflector IRA.

## 5.0 MEASUREMENTS

Antenna pattern and TDR measurements were carried out on a ground plane model of a half reflector IRA. The antenna was 12 inches (30.5 cm) in diameter, with an  $F/D$  of 0.25. The radiated field was measured, and comparisons were made to theory. A summary of this work appears in [5].

From TDR measurements, it was found that the impedance of the feed arms was not a uniform  $100\ \Omega$  with perfectly conical arms. The impedance started out at  $100\ \Omega$ , and then became lower as the feed arms approached the edge of the reflector. This was attributed to the proximity of the reflector. To raise the impedance to a more uniform  $100\ \Omega$ , the feed arms were tapered in various ways as they approached the edge of the reflector. In doing so, one can see an improvement in the uniformity of the feed impedance on the TDR measurement. The peak radiated field was also improved somewhat.

Experiments were also conducted which varied the impedance of the termination of the feed arms to the reflector. A matched load, a short circuit and an open circuit were considered. It was found that the matched load had some effect in damping out late-time oscillations, when compared to the other two termination impedances. Little effect was seen in the prepulse or in the magnitude of the radiated impulse.

Comparisons in the radiated field were made between the measurements and theory for both on- and off-boresight directions in the H-plane. The measured fields off-boresight demonstrated the double-hump characteristic in the impulse portion of the radiated field, as has been predicted by the theory. Furthermore, the measured beamwidth (peak field down by 0.707 of the boresight value) were in general agreement, with a measured value of 6 degrees, and a calculated value of 5 degrees. The magnitude of the peak measured field on boresight was about

half of what was predicted by the theory, as plotted in Figure 6. This is roughly consistent with the results obtained in [6], where the measured field was 0.53 times the predicted field. This might be attributed to any of a number of factors, including no correction for feed blockage in the theory, and imperfections in the geometry at the feed point.




Figure 6. A comparison of the boresight predicted and measured fields for a Half IRA.

- 
5. L. M. Atchley, G. D. Sower, and E. G. Farr, Scale-Model Ground-Plane Measurements of a Half IRA, Prototype IRA Memo 6, January 1996.
  6. E. G. Farr and C. A. Frost, "Compact Ultra-Short fuzing Antenna Design and Measurements," Sensor and Simulation Note 380, June 1995.

## 6.0 CONCLUSIONS

We have summarized here the most important results from our recent work in developing the half reflector IRA. We have provided a design for the lens, and we have calculated the field radiated from a typical aperture. Finally, we have provided measurements of ground-plane measurements of a half IRA. Additional details can be found in the notes that have been cited.

## DISTRIBUTION LIST

AUL/LSE Bldg 1405 - 600 Chennault Circle Maxwell AFB, AL 36112-6424	1 cy
DTIC/OCP 8725 John J. Kingman Rd, Suite 0944 Ft Belvoir, VA 22060-6218	2 cys
AFSAA/SAI 1580 Air Force Pentagon Washington, DC 20330-1580	1 cy
PL/SUL Kirtland AFB, NM 87117-5776	2 cys
PL/HO Kirtland AFB, NM 87117-5776	1 cy
Farr Research 614 Paseo Del Mar NE Albuquerque, NM 87123	3 cy
Official Record Copy PL/WSQ/William Prather	1 cy